



## **KEY FEATURES**

- Made in UK
- Compatible with all plug-in vehicle brands
- Up to 7.2kW
- Tethered (Type 2)
- 2-year product warranty
- Certified and compliant in accordance to TR25: 2016 (Singapore Standards)

## Looking for a discreet charger for your home?

MODEL ORDER CODE	EM002
Description	EO Mini 32A 1-Phase Charger
ELECTRIC DATA	
Rated Power	Up to 7.2kW
Charging Current	6A to 32A (variable)
Rated Current	Up to 32A max.
Nominal Supply	230VAC 50Hz
Supply Connections	L1, N, PE 2.5 - 10mm2
Over Current Protection	40A Supply
Earth Leakage Protection	A dedicated 30mA Type A RCD mnust be used on the supply circuit Integral 6mA DC leakage detection - no Type B RCD required
Standy Power Consumption	~3W
Status Indication	3 color LED indicator (green, blue, red)
Charging Mode	Mode 3 (IEC 61851-1 / SAE J1772 compliant communication protocol)
Tethered Type 2 plug connector, 5m cable	IEC 62196 Type 2
Supply Cable Entry	Ø 20mm or Ø25mm hole drilled at site through bottom of enclosure
MECHANICAL DATA	
Dimensions (H x W x D)	175mm x 125mm x 150mm – Tethered
Unit Weight	< 1.5kg
Mounting Location	Wall Mounted, Indoor or Outdoor (permanent mounting)
Ambient Temperature	- 10 °C to +50 °C
Operating Humidity	5 to 95%
Enclosure	ABS (UL94 HB Fire Rated), IKO8
Protection	IP54
Standard Finish	Glasuirt 68 Line Paint, Silver (RAL 9006)
COMPLIANCE	
	CE Marked, EMC Directive 2014/30/EU, IEC 61851-1, IEC 61851-22, IEC 62196-2 , TR25: 2016

In no event will EO Charging accept any liability for any loss, costs or damange consequential on the use and/or misuse of our hardware or software products except and only to the extent that this is caused by our negligence.



For more information on the **EO Mini**, contact: **EVSE Singapore Pte Ltd** 

8 Tuas View Loop Singapore 637674

Tel: +65 6896 6620

Email: enquiries@evse.com.sg Website: www.evse.com.sg